



Georg Kramp GmbH & Co.KG
 GKS-Perfekt lifting and moving systems
 Max-Planck-Straße 32, 70736 Fellbach/Germany
 tel.: +49 (0)711 / 510981- 0 - fax: +49 (0)711 / 510981- 90
 www.gks-perfekt.com - sales@gks-perfekt.com



possible field of application for GKS-hydraulic pumps

type of pumps	art.-no. GKS		usable reservoir cap.	application (jacks + rotating trolleys)
PV-K	11366	700 bar standard	0,33 ltr.	for high pressure cylinder/Powerteam
	10197	520 bar standard	0,33 ltr.	2 pcs. V5K-EX or 2 pcs. RLZ5
		420 bar manual adjusted	0,33 ltr.	2 pcs. RLZ4
		210 bar manual adjusted	0,33 ltr.	2 pcs. RLZ2K or 2 pcs. RLZ2
PV-M	11985	700 bar standard	0,74 ltr.	for high pressure cylinder/Powerteam
	11827	520 bar standard	0,74 ltr.	2 pcs. V5/V5EX or V10K-EX or 2 pcs. G5
PV	11336	700 bar standard	2,25 ltr.	for high pressure cylinder/Powerteam
	10198	520 bar standard	2,25 ltr.	2 pcs. V10/V10EX or 2 pcs. V15/V15EX/V15K-EX or 2 pcs. V20 or 2 pcs. G10
		430 bar manual adjusted	2,25 ltr.	1 pcs. V30EX (up to 300-400x strokes!!!)
PE	12023	700 bar standard	4,8 ltr.	for high pressure cylinder/Powerteam
	10199	520 bar standard	4,8 ltr.	each 4 pcs. V5/V5EX/V10/V10EX/V15/V20/G5/G10/RLZ5
	430 bar manual adjusted	4,8 ltr.	each 2 pcs. V30EX (extra charge for a two-fold distributor at the PE-pump!)